



4762

High Precision Current Range Extender (Current Comparator)



This electronically controlled current transformer is specifically designed for current range extension in capacitance measurements. It has divider measurements of 1:10 and 1:100.

The special transformer is accommodated inside a portable casing with all terminals on the top panel.

FEATURES & BENEFITS

- Especially suitable for range extension to measurement of high capacitances.
- Very wide operating current range
 $I_{\max} : I_{\min} = 4000 : 1$
- Very accurate measurement, even with heavy burdens
- Negligible transformer error eliminates calculation of measured C and $\tan \delta$ correction factors.

TECHNICAL SPECIFICATIONS

Current Ratio	1 : 10	1 : 100
min. primary current	10 mA	100 mA
max. primary current	40 A	400 A
min. secondary current	1 mA	1 mA
max. secondary current	4 A	4 A
Burden	Max. 1 Ω	
Current error	< 0.002 %	
Phase angle @ burden < 0.1 Ω	< 0.05 min or < 1.5×10^{-5} radian ($\tan \delta$)	
Phase angle @ burden < 1 Ω	< 0.15 min or < 4×10^{-5} radian ($\tan \delta$)	
Frequency Range	45 to 65 Hz	
Dimension LxWxH	305 x 180 x 255 mm (12 x 7.1 x 10")	
Weight	9.5 kg (20.9 lbs)	
Mains	230 or 115 VAC, 50/60 Hz	

SCOPE OF SUPPLY

Current Comparator 4762 (115 or 230V type -> specify in order), Mains cable

Europe, Asia, South & Central America, Australia

Haefely Test AG
Birsstrasse 300
4052 Basel
Switzerland
☎ + 41 61 373 4111
☎ + 41 61 373 4912
✉ sales@tettex.com

China (Sales & Service Office)

Haefely Test AG – Beijing Office
8-1-602, Fortune Street
No. 67, Chaoyang Road, Chaoyang District
Beijing, 100025
P. R. China
☎ + 86 10 8578 8099
☎ + 86 10 8578 9908
✉ sales@haefely.com.cn

North America

Hipotronics Inc.
1650 Route 22
PO Box 414
Brewster, NY 10509
USA
☎ + 1 845 279 3644
☎ + 1 845 279 2467
✉ sales@hipotronics.com

a brand of

HAEFELY



Haefely is a subsidiary
of Hubbell Incorporated.



a brand of

HAEFELY 



Haefely is a subsidiary
of Hubbell Incorporated.

