



5286 / 5287

Current Booster



GENERAL

The type 5286 and 5287 extends the performance of the C-tan δ field test sets 2818/ 5283, 2816/5284 U and MIDAS 2880.

The 5286 and 5287 provides an additional power supply with high current output and normal capacitances for on-site inductance testing. It comes into use for transformer on-site testing with

- compact design and portability
- integrated overload protection
- high current output up to 10 A

DESIGN FEATURES

The system is designed for on-site inductance testing, especially for short circuit impedance testing at power transformers.

The short circuit impedance of a winding is tested with the opposite (secondary) winding shorted. The requirement for the high current power supply and high accuracy measuring device is met with the 5286 in combination with the bridge 2818 or 2816 and the 5287 in combine with MIDAS2880.

TECHNICAL SPECIFICATIONS

- Current output 0 ... 10 A
- Max. current output 15 A for 5 min.
- Voltage output 0 ... 11 V or 0 ... 110 V
- Standard C approx. 100 nF

DIMENSIONS

- Dimensions 255 x 300 x 255 mm
- (w x h x d) (10 x 11.8 x 10 in.)
- Weight 21 kg (46 lbs)

SAFETY CIRCUITS

The current output is automatically interrupted when the current booster was overloaded. The interrupt is indicated at the front panel. After sufficient cooling of the power supply the system turns back into normal operating mode. The test complies with IEC 76-5

STANDARD SCOPE OF SUPPLY

5287 current booster including cable set for installation with MIDAS 2880



ORDER SPECIFICATIONS

- 5286 current booster including cable set for installation with 2818/5283
- 5286 current booster including cable set for installation with 2816/5284 U and modification of the 5284
- 5287 current booster including cable set for installation with MIDAS 2880

Europe, Asia, South & Central America, Australia

Haefely Test AG
Birsstrasse 300
4052 Basel
Switzerland
☎ + 41 61 373 4111
☎ + 41 61 373 4912
✉ sales@tettex.com

www.tettex.com

China (Sales & Service Office)

Haefely Test AG – Beijing Office
8-1-602, Fortune Street
No. 67, Chaoyang Road, Chaoyang District
Beijing, 100025
P. R. China
☎ + 86 10 8578 8099
☎ + 86 10 8578 9908
✉ sales@haefely.com.cn

North America

Hipotronics Inc.
1650 Route 22
PO Box 414
Brewster, NY 10509
USA
☎ + 1 845 279 3644
☎ + 1 845 279 2467
✉ sales@hipotronics.com

a brand of

HAEFELY



Haefely is a subsidiary
of Hubbell Incorporated.

