



5288A

33kVA, 10/12* kV Mobile Resonating Inductor for use with MIDAS System



The capacitive load range of the MIDAS system can be increased by using this Compensating Reactor (resonating inductor).

The 5288A provide a manual tuneable 10 kV*, 33 kVA inductor coil. It comes into use mainly for power generator or other high capacitive loads on-site testing.

FUNCTION

The variable inductor is connected in parallel with the capacitive test object C_x . This configuration constitutes a parallel resonant circuit.

By adjusting the inductor L_K the resonant point can be balanced.

In this resonant configuration the inductor compensates the reactive power required by the capacitor and only a smaller proportion of real power (ohmic losses) is taken from the main supply.

This arrangement enables measurement of capacitances up to $1\mu F$ at 10 kV.

Technical Specifications

Max. Operating Voltage	10 kV* rms (50 Hz / 60 Hz)
Frequency	50 / 60 Hz
Maximum Output Current	3.30 A @50 Hz 2.75 A @60 Hz
Maximum Output Power	33 kVA
Inductance range (typical)	9.7 H .. 250 H
Load tuning range	40nF .. 1 uF @50 Hz 28nF .. 725 nF @60 Hz
PD Level @ Max. Output	<500 pC
Duty cycle at full load	50% at rated output power over a 16h period. Max. ON time: 15minutes
Dimensions WxDxH	58 x 48 x 84cm (23 x 19 x 33")
Weight	135 kg (297 lbs)
Operating Temperature	+5 .. 50°C
Storage Temperature	-20 .. 70°C
Relative Humidity	5 .. 95 % r.h.
Dimensions	58 x 48 x 84 cm

*Max. 12 kV with reduced load

SCOPE OF SUPPLY

5288A resonating inductor including cable set (3m) for complete installation together with MIDAS system.

Europe, Asia, South & Central America, Australia

Haefely Test AG
Birsstrasse 300
4052 Basel
Switzerland
+ 41 61 373 4111
+ 41 61 373 4912
sales@tettex.com

a brand of

HAEFELY



China (Sales & Service Office)

Haefely Test AG – Beijing Office
8-1-602, Fortune Street
No. 67, Chaoyang Road, Chaoyang
District
Beijing, 100025
P. R. China
+ 86 10 8578 8099
+ 86 10 8578 9908
sales@haefely.com.cn

North America

Hipotronics Inc.
1650 Route 22
PO Box 414
Brewster, NY 10509
USA
+ 1 845 279 3644
+ 1 845 279 2467
sales@hipotronics.com

Haefely is a subsidiary
of Hubbell Incorporated.

